

M842-20 K9 bolt



P1500 RF Receiver Specifications

- Range - 300 Feet Typical
- Up to 600 Feet
- Output - 1, 2 & 4 Relays
- Input - 2 (+12v)
- Frequency - 433MHz
- Codes - Rolling Codes
- Secure Encryption
- Voltage - 12VDC
- 24VDC
- Current - 5 Amps Max per Output
- 10 Amp Input
- Harness - 9" Standard, 8 pin
- Output - All +12v @ 5 Amps Ea
- Voltage - All Ground @ 500 mAmps Ea



P1500 Series
Standard Unsealed
5 1/4" x 3"

1 Button Sealed Transmitter



- | |
|---|
| <p>Battery</p> <ul style="list-style-type: none"> - Coin Style, Lithium, CR2032 - 100,000 1-second pulses - 10 year shelf life |
|---|

M842-20 K9 Bolt Kit

- | | | |
|---|------------------------------|------------|
| 1 | - Receiver | P1500-R1 |
| 2 | - Transmitter | P1000-TK1 |
| 1 | - Duty Belt Holster | DBH10441-3 |
| 1 | - 30 LB Gas Strut | GSSxxxxx-x |
| 1 | - Solenoid or Actuator | SOLxxxxx-x |
| 1 | - Miscellaneous Hardware Kit | HDWxxxxx-x |
| 1 | - Harness | HNSxxxxx-x |
| 1 | - Owners Manual | NSTxxxxx-x |

Call TouchTronics, Inc., Sales for
Additional Information, Samples and Pricing
1-800-294-2570 (Inside US)
1-574-294-2570 (Outside US)

Designed & Manufactured in the **USA** since 1984